

EPOS4

Feature Chart

maxon motor control's EPOS4 products are small-sized, full digital, smart positioning control units. Their high power density allows flexible use for brushed DC and brushless EC (BLDC) motors up to approximately 1'050 Watts with various feedback options, such as Hall sensors, incremental encoders as well as absolute sensors in a multitude of drive applications.

EPOS4 controllers are specially designed to be commanded and controlled as a slave node in a CANopen or EtherCAT network. In addition, the units can be operated via any USB or RS232 communication port of a Windows or Linux workstation. Moreover, the integrated extension interface allows pooling with optionally available communication interfaces or other additional functionalities.

Latest technology, such as field-oriented control (FOC), acceleration/velocity feed forward and dual loop control in combination with highest control cycle rates allow sophisticated, ease-of-use motion control.



epos.maxonmotor.com

Legend:

✓ = included / (✓) = on request / nnnnn = order number / ** = available shortly / (a) requires an optionally available extension card (see "Accessories" on page 5 and page 12) / (b) optional for separate logic supply / (c) mandatory for supply of power stage / (d) with suitable motherboard

Product Overview

Modules

Module

Find details as of page 2

CANopen **EtherCAT** 

EPOS4 Module 24/1.5



EPOS4 Module 50/5



EPOS4 Module 50/8



EPOS4 Module 50/15



Ready-to-connect Units

Compact CAN

Find details as of page 6

CANopen

EPOS4 Compact 24/1.5 CAN



EPOS4 Compact 50/5 CAN



EPOS4 Compact 50/8 CAN



EPOS4 Compact 50/15 CAN

**Compact EtherCAT**

Find details as of page 6

EtherCAT 

EPOS4 Compact 24/1.5 EtherCAT



EPOS4 Compact 50/5 EtherCAT



EPOS4 Compact 50/8 EtherCAT



EPOS4 Compact 50/15 EtherCAT

**Encased Housing**

Find details as of page 6

CANopen **EtherCAT** 

EPOS4 50/5



EPOS4 70/15



Modules	EPOS4 Module 24/1.5 (536630)	EPOS4 Module 50/5 (534130)	EPOS4 Module 50/8 (504384)	EPOS4 Module 50/15 (504383)
 for comparison purposes: US Half Dollar coin (Ø30.6 mm)				
Communication Interfaces				
CANopen Slave			max. 1 Mbit/s	
CANopen Application Layer and Communication Profile			CiA 301	
CANopen Layer Setting Services and Protocol (LSS)			CiA 305**	
CANopen Device Profile Drives and Motion Control			CiA 402	
USB 2.0 / USB 3.0			Full speed	
Gateway function USB-to-CAN			✓	
RS232			max. 115'200 bit/s	
Gateway function RS232-to-CAN			✓	
EtherCAT Slave			✓ (a)	
IEC 61158 Digital data communication for measurement and control Fieldbus for use in industrial control systems			Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	
IEC 61800-7 Generic interface and use of profiles for power drive systems			Profile type 1 (CiA 402)	
CAN application layer over EtherCAT (CoE)			✓	
File transfer over EtherCAT (FoE)			✓	
Distributed clocks support			✓	
Cyclic modes support cycle times down to...			1 ms	
Process data			PDO mapping (Variable)	
Motors				
Brushed DC motors up to (continuous / max.)	36 W / 108 W	250 W / 750 W	400 W / 1'500 W	750 W / 1'500 W
Brushless EC motors (BLDC) up to (continuous / max.)	36 W / 108 W	250 W / 750 W	400 W / 1'500 W	750 W / 1'500 W
Sensors (Feedback)				
Digital Hall sensors (EC motors)			✓	
Digital incremental encoder (2-/3-channel, single-ended or differential)			✓	
Analog incremental encoder (3-channel, sin/cos, differential)			✓	
SSI absolute encoder (configurable)			✓	
BiSS C absolute encoder (configurable)			(✓) (a)	
EnDat 2.2 absolute encoder (configurable)			(✓) (a)	
Commutation				
Digital Hall sensors			✓	
Digital Hall sensors + digital incremental encoder			✓	
Digital Hall sensors + analog incremental encoder			✓	
Digital Hall sensors + absolute encoder			✓	
Absolute encoder			✓	
Electrical Data				
Nominal power supply voltage (+V _{CC})	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC
Nominal logic supply voltage (+V _C)	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC
Absolute supply voltage limits (+V _{min} / +V _{max})	8 VDC / 28 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC
Output voltage (max.)		0.9 x +V _{CC}		
Output current (I _{cont} / I _{max})	1.5 A / 4.5 A (<30 s)	5 A / 15 A (<3 s)	8 A / 30 A (<5 s)	15 A / 30 A (<60 s)
Pulse width modulation frequency	100 kHz	50 kHz	50 kHz	50 kHz
Sampling rate PI current controller		25 kHz (40 µs)		
Sampling rate PID speed controller		2.5 kHz (400 µs)		
Sampling rate PID positioning controller		2.5 kHz (400 µs)		
Max. efficiency	89%	97%	98%	98%
Max. speed DC motor		limited by max. permissible speed (motor)		
Max. speed EC motor, block commutation		100'000 rpm (1 pole pair)		
Max. speed EC motor, sinusoidal commutation		50'000 rpm (1 pole pair)		
Built-in motor choke		—		

Modules	EPOS4 Module 24/1.5 (536630)	EPOS4 Module 50/5 (534130)	EPOS4 Module 50/8 (504384)	EPOS4 Module 50/15 (504383)
Inputs / Outputs				
Digital Hall sensor signals		H1, H2, H3 (+2...+24 VDC, internal pull-up)		
Digital incremental encoder signals		A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz)		
Encoder signals		A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz)	Clock, Clock\	
Digital incremental, analog incremental, absolute serial SSI, BiSS (a), EnDat (a)		Data, Data\		
Digital inputs		4 (+2.1...+36 VDC)		
Digital outputs		2 (open collector, max. 36 VDC / 500 mA, internal pull-up)		
High-speed digital inputs		4 (EIA RS422, 6.25 MHz)		
High-speed digital outputs		1 (EIA RS422, 6.25 MHz)		
Analog inputs		2 (resolution 12-bit, -10...+10 V, 10 kHz, differential)		
Analog outputs		2 (resolution 12-bit, -4...+4 V, 25 kHz)		
STO inputs		2 (+4.5...+30 VDC, optically isolated)		
STO outputs		1 (max. 30 VDC / 15 mA, optically isolated with self-resetting short-circuit protection)		
Sensor supply voltage		+5 VDC ($I_L \leq 100$ mA)		
Auxiliary output voltage		+5 VDC ($I_L \leq 150$ mA)		
Status indicators (LEDs or bi-color LEDs)		Device status		
Connections				
A1...A46 Power Supply Logic Supply Motor ($I_{cont} \leq 11$ A) Hall Sensor Encoder	Box header (1.27 mm) 2x23 poles	Box header (1.27 mm) 2x23 poles	Pin header (2.54 mm) 2x16 poles	Pin header (2.54 mm) 2x16 poles
B1...B46 Sensor Digital I/O Analog I/O STO RS232 CAN	Box header (1.27 mm) 2x23 poles	Box header (1.27 mm) 2x23 poles	Pin header (2.54 mm) 2x23 poles	Pin header (2.54 mm) 2x23 poles
X13 USB		USB Type micro B, female		
Mechanical Data				
Weight (approximate)	17 g	17 g	23 g	70 g
Dimensions (L x W x H)	53.8 x 38.8 x 11.1 mm	53.8 x 38.8 x 11.1 mm	59.5 x 46.0 x 14.1 mm	59.5 x 62.0 x 16.4 mm
Mounting	Pluggable (female headers 1.27 mm) or M2.5 screws	Pluggable (female headers 1.27 mm) or M2.5 screws	Pluggable (female headers 2.54 mm) or M2.5 screws	Pluggable (female headers 2.54 mm) or M3 screws
Environmental Conditions				
Temperature – Operation	-30...+60 °C	-30...+45 °C	-30...+45 °C	-30...+25 °C
Temperature – Extended range and derating	+60...+73 °C / -0.115 A/°C	+45...+75 °C / -0.167 A/°C	+45...+77 °C / -0.250 A/°C	+25...+77 °C / -0.288 A/°C
Temperature – Storage			-40...+85 °C	
Altitude – Operation			0...6'000 m MSL	
Altitude – Extended range			6'000...10'000 m MSL (for derating see «Hardware Reference»)	
Humidity (condensation not permitted)			5...90%	
Directives & Standards				
Generic		IEC/EN 61000-6-2; IEC/EN 61000-6-3		
Applied		IEC/EN 55022 (CISPR22); IEC/EN 61000-4-3; IEC/EN 61000-4-4; IEC/EN 61000-4-6		
Environment		IEC/EN 60068-2-6; MIL-STD-810F		
Safety (UL File Number; unassembled PCB)	E207844	E207844	E76251; E207844; E337862	E76251; E207844; E337862
Reliability (MIL-HDBK-217F; MTBF)	611'610 hours	314'822 hours	245'451 hours	240'400 hours, with heat sink <3.1 K/W
Functionality				
Operating Modes				
CST	Cyclic Synchronous Torque Mode		✓	
CSV	Cyclic Synchronous Velocity Mode		✓	
CSP	Cyclic Synchronous Position Mode		✓	
PVM	Profile Velocity Mode		✓	
PPM	Profile Position Mode		✓	
IPM	Interpolated Position Mode		(✓)	
HMM	Homing Mode		✓	
Master Encoder Functionality			(✓)	
Step/Direction Functionality			(✓)	
Analog Set Value Functionality			✓**	
Features				
Feed forward (acceleration/velocity for inertia and friction compensation)			✓	
Field-oriented Control (FOC)			✓	
Velocity observer			✓	
Dual loop control			✓	
Standalone programmability			(✓)	
Custom persistent memory			✓	
Advanced automatic control settings (Auto Tuning)			✓	
Safe Torque Off (based on IEC/EN 61800-5-2, certification pending)			✓	

Modules	EPOS4 Module 24/1.5 (536630)	EPOS4 Module 50/5 (534130)	EPOS4 Module 50/8 (504384)	EPOS4 Module 50/15 (504383)
Digital I/O Functionality				
Inputs (configurable)			✓	
Touch Probe			(✓)	
Reference switches			✓	
Limit switches			✓	
Quickstop			✓	
Drive Enable			✓	
General purpose			✓	
Outputs (configurable)			✓	
Position Compare			(✓)	
Holding Brake			✓	
Ready/Fault			✓	
General purpose			✓	
Analog I/O Functionality				
Inputs (configurable)			✓	
Analog set value			✓**	
General purpose			✓	
Outputs (configurable)			✓**	
Current monitor			✓**	
Velocity monitor			✓**	
Position monitor			✓**	
Temperature monitor			✓**	
General purpose			✓	
Built-in Protection				
Current limiter (adjustable)			✓	
Overcurrent			✓	
Thermal motor protection			✓	
Thermal controller protection			✓	
Overvoltage			✓	
Undervoltage			✓	
Voltage transients			✓	
Short-circuit of motor winding			✓	
Loss of feedback signal			✓	
Following error			✓	
Status reporting			✓	
Firmware error handling			✓	
Software				
Installation Program			EPOS Setup	
Graphical User Interface			EPOS Studio	 <small>EPOS Tutorials on Vimeo</small>
	<p>The EPOS video library features video tutorials that provide easy to follow instructions on how to get started with «EPOS Studio» and shows you tips and tricks on how to setup communication interfaces, motors and sensors, and so on.</p> <p>Explore on Vimeo: https://vimeo.com/album/4646388</p>			
Startup			✓	
Regulation Tuning			✓	
Firmware Update			✓	
Motion Commander			✓	
I/O Monitor			✓	
Parameters			✓	
Data Recording			✓	
Command Analyzer			✓	
CANopen Wizard			✓	
Online Help			✓	
Language			English	
Operating System			Windows 10, 8, 7	
Windows DLL for PC			32-bit / 64-bit	
CAN interfaces			IXXAT National Instruments Kvaser Vector	
Programming examples		Microsoft Visual Basic, Visual Basic.NET, Visual C#, Visual C++ Borland C++, Delphi National Instruments LabView, LabWindows/CVI		
Linux Shard Object Library		X86 32-bit/64-bit, ARMv6/v7/v8 32-bit, ARMv8 64-bit		
CAN interfaces		IXXAT Kvaser		
Programming examples		C++		

Modules	EPOS4 Module 24/1.5 (536630)	EPOS4 Module 50/5 (534130)	EPOS4 Module 50/8 (504384)	EPOS4 Module 50/15 (504383)
Accessories (not included in delivery)				
403968 USB Type A - micro B Cable	✓	✓	✓	✓
536997 EPOS4 CB 24/1.5 CAN	✓	—	—	—
620048 EPOS4 CB 24/1.5 EtherCAT	✓	—	—	—
534133 EPOS4 CB 50/5 CAN	—	✓	—	—
620044 EPOS4 CB 50/5 EtherCAT	—	✓	—	—
520884 EPOS4 CB Power CAN	—	—	✓	✓
604594 EPOS4 CB Power EtherCAT	—	—	✓	✓
581245 EPOS4 EtherCAT Card	✓ (d)	✓ (d)	✓ (d)	✓ (d)

Ready-to-connect Units	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 Compact 24/1.5 EtherCAT (628092)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Compact 50/5 EtherCAT (628094)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Compact 50/8 EtherCAT (605298)	EPOS4 Compact 50/15 CAN (520886)	EPOS4 Compact 50/15 EtherCAT (605299)	EPOS4 50/5 (546047)	EPOS4 70/15 (594385)
 for comparison purposes: US Half Dollar coin (Ø30.6 mm)										
Communication Interfaces										
CANopen Slave	max. 1 Mbit/s	—	max. 1 Mbit/s	—	max. 1 Mbit/s	—	max. 1 Mbit/s	—	max. 1 Mbit/s	max. 1 Mbit/s
CANopen Application Layer and Communication Profile	CiA 301	—	CiA 301	—	CiA 301	—	CiA 301	—	CiA 301	CiA 301
CANopen Layer Setting Services and Protocol (LSS)	CiA 305**	—	CiA 305**	—	CiA 305**	—	CiA 305**	—	CiA 305**	CiA 305**
CANopen Device Profile Drives and Motion Control	CiA 402	—	CiA 402	—	CiA 402	—	CiA 402	—	CiA 402	CiA 402
USB 2.0 / USB 3.0										
Full speed										
Gateway function USB-to-CAN	✓	—	✓	—	✓	—	✓	—	✓	✓
RS232	max. 115'200 bit/s	—	max. 115'200 bit/s	—	max. 115'200 bit/s	—	max. 115'200 bit/s	—	max. 115'200 bit/s	max. 115'200 bit/s
Gateway function RS232-to-CAN	✓	—	✓	—	✓	—	✓	—	✓	✓
EtherCAT Slave	—	✓	—	✓	—	✓	—	✓	✓ (a)	✓ (a)
IEC 61158 Digital data communication for measurement and control Fieldbus for use in industrial control systems	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	—	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)	Type 12 (EtherCAT) max. 100 Mbit/s (100 Base Tx)
IEC 61800-7 Generic interface and use of profiles for power drive systems	—	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	—	Profile type 1 (CiA 402)	Profile type 1 (CiA 402)	Profile type 1 (CiA 402)
CAN application layer over EtherCAT (CoE)	—	✓	—	✓	—	✓	—	✓	✓	✓
File transfer over EtherCAT (FoE)	—	✓	—	✓	—	✓	—	✓	✓	✓
Distributed clocks support	—	✓	—	✓	—	✓	—	✓	✓	✓
Cyclic modes support cycle times down to...	—	1 ms	—	1 ms	—	1 ms	—	1 ms	1 ms	1 ms
Process data	—	PDO mapping (Variable)	—	PDO mapping (Variable)	—	PDO mapping (Variable)	—	PDO mapping (Variable)	PDO mapping (Variable)	PDO mapping (Variable)
Motors										
Brushed DC motors up to (continuous / max.)	36 W / 108 W	36 W / 108 W	250 W / 750 W	250 W / 750 W	400 W / 1'500 W	400 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W	250 W / 750 W	1'050 W / 2'100 W
Brushless EC motors (BLDC) up to (continuous / max.)	36 W / 108 W	36 W / 108 W	250 W / 750 W	250 W / 750 W	400 W / 1'500 W	400 W / 1'500 W	750 W / 1'500 W	750 W / 1'500 W	250 W / 750 W	1'050 W / 2'100 W
Sensors (Feedback)										
Digital Hall sensors (EC motors)	✓									
Digital incremental encoder (2-/3-channel, single-ended or differential)	✓									
Analog incremental encoder (3-channel, sin/cos, differential)	✓									
SSI absolute encoder (configurable)	✓									
BiSS C absolute encoder (configurable)	—	—	—	—	—	—	—	—	(✓) (a)	(✓) (a)
EnDat 2.2 absolute encoder (configurable)	—	—	—	—	—	—	—	—	(✓) (a)	(✓) (a)
Commutation										
Digital Hall sensors	✓									
Digital Hall sensors + digital incremental encoder	✓									
Digital Hall sensors + analog incremental encoder	✓									
Digital Hall sensors + absolute encoder	✓									
Absolute encoder	✓									

Ready-to-connect Units	EPOS4 Compact 24/1.5		EPOS4 Compact 50/5		EPOS4 Compact 50/8		EPOS4 Compact 50/15		EPOS4 50/5 (546047)	EPOS4 70/15 (594385)
	CAN (546714)	EtherCAT (628092)	CAN (541718)	EtherCAT (628094)	CAN (520885)	EtherCAT (605298)	CAN (520886)	EtherCAT (605299)		
Electrical Data										
Nominal power supply voltage (+V _{CC})	10...24 VDC	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...70 VDC
Nominal logic supply voltage (+V _C)	10...24 VDC	10...24 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...50 VDC	10...70 VDC
Absolute supply voltage limits (+V _{min} / +V _{max})	8 VDC / 28 VDC	8 VDC / 28 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 56 VDC	8 VDC / 75 VDC
Output voltage (max.)	0.9 x +V _{CC}									
Output current (I _{cont} / I _{max})	1.5 A / 4.5 A (<30 s)	1.5 A / 4.5 A (<30 s)	5 A / 15 A (<3 s)	5 A / 15 A (<3 s)	8 A / 30 A (<5 s)	8 A / 30 A (<5 s)	15 A / 30 A (<60 s)	15 A / 30 A (<60 s)	5 A / 15 A (<15s)	15 A / 30 A (<60 s)
Pulse width modulation frequency	100 kHz	100 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz	50 kHz
Sampling rate PI current controller	25 kHz (40 µs)									
Sampling rate PID speed controller	2.5 kHz (400 µs)									
Sampling rate PID positioning controller	2.5 kHz (400 µs)									
Max. efficiency	89%	88%	97%	97%	98%	98%	98%	98%	98%	98%
Max. speed DC motor	limited by max. permissible speed (motor)									
Max. speed EC motor, block commutation	100'000 rpm (1 pole pair)									
Max. speed EC motor, sinusoidal commutation	50'000 rpm (1 pole pair)									
Built-in motor choke	3 x 94 µH; 1.5 A	3 x 100 µH; 1.5 A	3 x 9.4 µH; 5 A	3 x 10 µH; 5 A	3 x 2.2 µH; 15 A	3 x 2.2 µH; 15 A	3 x 2.2 µH; 15 A	3 x 2.2 µH; 15 A	3 x 15 µH; 5 A	3 x 15 µH; 15 A
Inputs / Outputs										
Digital Hall sensor signals	H1, H2, H3 (+2...+24 VDC, internal pull-up)									
Digital incremental encoder signals	A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz)									
Encoder signals	A, A\, B, B\, I, I\ (EIA RS422, 6.25 MHz)									
Digital incremental, analog incremental, absolute serial SSI, BiSS (a), EnDat (a)	Clock, Clock\ Data, Data\									
Digital inputs	4; level selectable by DIP switch: (Logic level: +2.0...+30 VDC) or (PLC level: +9.0...+30 VDC)									
Digital outputs	2 (open collector, max. 36 VDC / 500 mA, internal pull-up)									
High-speed digital inputs	4 (EIA RS422, 6.25 MHz)									
High-speed digital outputs	1 (EIA RS422, 6.25 MHz)									
Analog inputs	2 (resolution 12-bit, -10...+10 V, 10 kHz, differential)									
Analog outputs	2 (resolution 12-bit, -4...+4 V, 25 kHz)									
STO inputs	2 (+4.5...+30 VDC, optically isolated)									
STO outputs	1 (max. 30 VDC / 15 mA, optically isolated with self-resetting short-circuit protection)									
Sensor supply voltage	+5 VDC (I _L ≤100 mA)									
Auxiliary output voltage	+5 VDC (I _L ≤150 mA)									
Status indicators (LEDs or bi-color LEDs)	Device status									
	—	NET status	—	NET status	—	NET status	—	NET status	NET port	NET port
	—	NET port	—	NET port	—	NET port	—	NET port	NET port	NET port

Ready-to-connect Units	EPOS4 Compact 24/1.5		EPOS4 Compact 50/5		EPOS4 Compact 50/8		EPOS4 Compact 50/15		EPOS4 50/5 (546047)	EPOS4 70/15 (594385)
	CAN (546714)	EtherCAT (628092)	CAN (541718)	EtherCAT (628094)	CAN (520885)	EtherCAT (605298)	CAN (520886)	EtherCAT (605299)		
Connections										
X1 Power Supply	—	—	—	—	Molex Mega-Fit 2 poles	Molex Mini-Fit Jr. 2 poles	Molex Mega-Fit 2 poles			
X2 Logic Supply	—	—	—	—	Molex Mini-Fit Jr. 2 poles	Molex Mini-Fit Jr., 2 poles	Molex Mini-Fit Jr. 2 poles			
X1/X2 Power & Logic Supply	Harting har-flexicon 3 poles	—	—	—	—	—	—			
X3 Motor	—	—	Molex Mini-Fit Jr. 4 poles	Molex Mini-Fit Jr. 4 poles	—	—	—	—	Molex Mini-Fit Jr. 4 poles	—
X3a Motor ($I_{cont} \leq 11$ A)	—	—	—	—	Molex Mini-Fit Jr. 4 poles	—	Molex Mini-Fit Jr. 4 poles			
X3b Motor ($I_{cont} \leq 15$ A)	—	—	—	—	—	—	Molex Mega-Fit 4 poles	Molex Mega-Fit 4 poles	—	Molex Mega-Fit 4 poles
X3c Motor	Hirose DF3DZ 3 poles	Hirose DF3DZ 3 poles	—	—	—	—	—	—	—	—
X3a/X4a Motor & Hall Sensor	Harting har-flexicon 8 poles	Harting har-flexicon 8 poles	—	—	—	—	—	—	—	—
X3b/X4b Motor & Hall Sensor	Lumberg Minimodul 8 poles	Lumberg Minimodul 8 poles	—	—	—	—	—	—	—	—
X4 Hall Sensor	—	—	Molex Micro-Fit 3.0 6 poles							
X5 Encoder	Pin header 2.54 mm 2x5 poles									
X6 Sensor	Molex CLIK-Mate 2x5 poles									
X7 Digital I/O	Molex CLIK-Mate 8 poles									
X8 Analog I/O	Molex CLIK-Mate 7 poles									
X9 STO	Molex CLIK-Mate 8 poles									
X10 RS232	Molex CLIK-Mate 5 poles	—	Molex CLIK-Mate 5 poles	Molex CLIK-Mate 5 poles						
X11 CAN 1	Molex CLIK-Mate 4 poles	—	Molex CLIK-Mate 4 poles	Molex CLIK-Mate 4 poles						
X12 CAN 2	Molex CLIK-Mate 4 poles	—	Molex CLIK-Mate 4 poles	Molex CLIK-Mate 4 poles						
X13 USB	USB Type micro B, female									
X14 Extension IN (a)	—	RJ45 10/100-BASE-TX	RJ45 10/100-BASE-TX	RJ45 10/100-BASE-TX						
X15 Extension OUT (a)	—	RJ45 10/100-BASE-TX	RJ45 10/100-BASE-TX	RJ45 10/100-BASE-TX						
X16 Extension Signal (a)	—	—	—	—	—	—	—	—	Molex CLIK-Mate 2x5 poles	Molex CLIK-Mate, 2x5 poles

Ready-to-connect Units	EPOS4 Compact 24/1.5		EPOS4 Compact 50/5		EPOS4 Compact 50/8		EPOS4 Compact 50/15		EPOS4 50/5 (546047)	EPOS4 70/15 (594385)
	CAN (546714)	EtherCAT (628092)	CAN (541718)	EtherCAT (628094)	CAN (520885)	EtherCAT (605298)	CAN (520886)	EtherCAT (605299)		
Mechanical Data										
Weight (approximate)	58 g	78 g	58 g	76 g	86 g	100 g	126 g	140 g	206 g	372 g
Dimensions (L x W x H) [mm]	55.0 x 40.0 x 31.1	56.5 x 55.0 x 31.7	55.0 x 40.0 x 31.1	56.5 x 55.0 x 31.7	59.5 x 58.5 x 33.0	59.5 x 79.5 x 35.7	59.5 x 65.5 x 35.1	59.5 x 79.5 x 37.0	105.0 x 83.0 x 38.7	125.0 x 94.5 x 38.7
Mounting	M2.5 screws	M2.5 screws	M2.5 screws	M2.5 screws	M2.5 screws	M2.5 screws	M3 screws	M3 screws	M4 screws	M4 screws
Environmental Conditions										
Temperature – Operation	-30...+45 °C	-30...+45 °C	-30...+25 °C	-30...+25 °C	-30...+45 °C	-30...+45 °C	-30...+25 °C	-30...+25 °C	-30...+50 °C	-30...+50 °C
Temperature – Extended range and derating	+45...+70 °C -0.060 A/°C	+45...+70 °C -0.060 A/°C	+25...+70 °C -0.111 A/°C	+25...+70 °C -0.111 A/°C	+45...+77 °C -0.250 A/°C	+45...+77 °C -0.250 A/°C	+25...+77 °C -0.288 A/°C	+25...+77 °C -0.288 A/°C	+50...+80 °C -0.167 A/°C	+50...+85 °C -0.429 A/°C
Temperature – Storage							-40...+85 °C			
Altitude – Operation							0...6'000 m MSL			
Altitude – Extended range							6'000...10'000 m MSL (for derating see «Hardware Reference»)			
Humidity (condensation not permitted)							5...90%			
Directives & Standards										
Generic							IEC/EN 61000-6-2; IEC/EN 61000-6-3			
Applied							IEC/EN 55022 (CISPR22); IEC/EN 61000-4-3; IEC/EN 61000-4-4; IEC/EN 61000-4-6			
Environment							IEC/EN 60068-2-6; MIL-STD-810F			
Safety (UL File Number; unassembled PCB)	E207844	E207844	E207844	E207844	E76251; E116354; E207844; E337862	E76251; E207844; E337862; E133472	E76251; E116354; E207844; E337862	E76251; E207844; E337862; E133472	E229342	E207844
Reliability (MIL-HDBK-217F; MTBF)	326'977 hours	279'388 hours	253'865 hours	238'623 hours	210'109 hours	197'129 hours	199'049 hours, with heat sink <3.1 K/W	179'777 hours, with heat sink <3.1 K/W	296'741 hours	254'446 hours
Functionality										
Operating Modes										
CST	Cyclic Synchronous Torque Mode							✓		
CSV	Cyclic Synchronous Velocity Mode							✓		
CSP	Cyclic Synchronous Position Mode							✓		
PVM	Profile Velocity Mode							✓		
PPM	Profile Position Mode							✓		
IPM	Interpolated Position Mode							(✓)		
HMM	Homing Mode							✓		
Master Encoder Functionality								(✓)		
Step/Direction Functionality								(✓)		
Analog Set Value Functionality								✓**		
Features										
Feed forward (acceleration/velocity for inertia and friction compensation)								✓		
Field-oriented Control (FOC)								✓		
Velocity observer								✓		
Dual loop control								✓		
Standalone programmability								(✓)		
Custom persistent memory								✓		
Advanced automatic control settings (Auto Tuning)								✓		
Safe Torque Off (based on IEC/EN 61800-5-2, certification pending)								✓		

Ready-to-connect Units	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 Compact 50/5 EtherCAT (628092)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Compact 50/8 EtherCAT (628094)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Compact 50/15 EtherCAT (605298)	EPOS4 Compact 50/15 CAN (520886)	EPOS4 Compact 50/15 EtherCAT (605299)	EPOS4 50/5 (546047)	EPOS4 70/15 (594385)
Digital I/O Functionality										
Inputs (configurable)						✓				
Touch Probe						(✓)				
Reference switches						✓				
Limit switches						✓				
Quickstop						✓				
Drive Enable						✓				
General purpose						✓				
Outputs (configurable)						✓				
Position Compare						(✓)				
Holding Brake						✓				
Ready/Fault						✓				
General purpose						✓				
Analog I/O Functionality										
Inputs (configurable)						✓				
Analog set value						✓**				
General purpose						✓				
Outputs (configurable)						✓**				
Current monitor						✓**				
Velocity monitor						✓**				
Position monitor						✓**				
Temperature monitor						✓**				
General purpose						✓				
Built-in Protection										
Current limiter (adjustable)						✓				
Overcurrent						✓				
Thermal motor protection						✓				
Thermal controller protection						✓				
Overvoltage						✓				
Undervoltage						✓				
Voltage transients						✓				
Short-circuit of motor winding						✓				
Loss of feedback signal						✓				
Following error						✓				
Status reporting						✓				
Firmware error handling						✓				

Ready-to-connect Units	EPOS4 Compact 24/1.5 CAN (546714)	EPOS4 Compact 50/5 EtherCAT (628092)	EPOS4 Compact 50/5 CAN (541718)	EPOS4 Compact 50/8 EtherCAT (628094)	EPOS4 Compact 50/8 CAN (520885)	EPOS4 Compact 50/15 EtherCAT (605298)	EPOS4 Compact 50/15 CAN (520886)	EPOS4 Compact 50/15 EtherCAT (605299)	EPOS4 50/5 (546047)	EPOS4 70/15 (594385)	
Software											
Installation Program						EPOS Setup					
Graphical User Interface						EPOS Studio					
											
						The EPOS video library features video tutorials that provide easy to follow instructions on how to get started with «EPOS Studio» and shows you tips and tricks on how to setup communication interfaces, motors and sensors, and so on. Explore on Vimeo: → https://vimeo.com/album/4646388					
Startup						✓					
Regulation Tuning						✓					
Firmware Update						✓					
Motion Commander						✓					
I/O Monitor						✓					
Parameters						✓					
Data Recording						✓					
Command Analyzer						✓					
CANopen Wizard						✓					
Online Help						✓					
Language						English					
Operating System						Windows 10, 8, 7					
Windows DLL for PC						32-bit / 64-bit					
CAN interfaces						IXXAT National Instruments Kvaser Vector					
Programming examples						Microsoft Visual Basic, Visual Basic.NET, Visual C#, Visual C++ Borland C++, Delphi National Instruments LabView, LabWindows/CVI					
Linux Shared Object Library						X86 32-bit/64-bit, ARMv6/v7/v8 32-bit, ARMv8 64-bit					
CAN interfaces						IXXAT Kvaser					
Programming examples						C++					

Ready-to-connect Units	EPOS4 Compact 24/1.5		EPOS4 Compact 50/5		EPOS4 Compact 50/8		EPOS4 Compact 50/15		EPOS4 50/5 (546047)	EPOS4 70/15 (594385)
	CAN (546714)	EtherCAT (628092)	CAN (541718)	EtherCAT (628094)	CAN (520885)	EtherCAT (605298)	CAN (520886)	EtherCAT (605299)		
Accessories (not included in delivery)										
520858 CAN-CAN Cable	✓	—	✓	—	✓	—	✓	—	✓	✓
520857 CAN-COM Cable	✓	—	✓	—	✓	—	✓	—	✓	✓
275934 Encoder Cable	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
422827 Ethernet Cable	—	✓	—	✓	—	✓	—	✓	✓	✓
275878 Hall Sensor Cable	—	—	✓	✓	✓	✓	✓	✓	✓	✓
275851 Motor Cable	—	—	✓	✓	✓	✓	✓	✓	✓	✓
520851 Motor Cable High Current	—	—	—	—	—	—	✓	✓	—	✓
275829 Power Cable	—	—	—	—	✓ (b)	✓ (b)	✓ (b)	✓ (b)	✓	✓ (b)
520850 Power Cable High Current	—	—	—	—	✓ (c)	✓ (c)	✓ (c)	✓ (c)	—	✓ (c)
520856 RS232-COM Cable	✓	—	✓	—	✓	—	✓	—	✓	✓
520852 Sensor Cable 5x2core	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
520854 Signal Cable 7core	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
520853 Signal Cable 8core	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
403968 USB Type A - micro B Cable	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
520860 STO Idle Connector	✓ (included)	✓ (included)	✓ (included)	✓ (included)	✓ (included)	✓ (included)	✓ (included)	✓ (included)	✓ (included)	✓ (included)
520859 EPOS4 Connector Set	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
581245 EPOS4 EtherCAT Card	—	—	—	—	—	—	—	—	✓	✓

Copyright

In the present document, registered brand names are not tagged with their respective trademark. It must be understood that the brands (below list is not necessarily concluding) are protected by copyright and/or other intellectual property rights even if their legal trademarks are omitted.

BiSS	© iC-Haus GmbH, DE-Bodenheim
Borland®, Borland C++	© Borland Software Corporation, USA-Rockville MD
CANopen®, CiA®	© CiA CAN in Automation e.V., DE-Nuremberg
CLIK-Mate™, Micro-Fit™, Mini-Fit Jr.™, Mega-Fit®	© Molex, USA-Lisle, IL
Eclipse™	© Eclipse Foundation, Inc., CDN-Ottawa ON
EnDat	© DR. JOHANNES HEIDENHAIN GmbH, DE-Traunreut
EtherCAT®	© EtherCAT Technology Group, DE-Nuremberg, licensed by Beckhoff Automation GmbH, DE-Verl
har-flexicon®	© HARTING AG & Co. KG, DE-Espelkamp
LabVIEW™, LabWindows™, NI SoftMotion™	© National Instruments Corporation, USA-Austin TX
Linux®	© Linus Torvalds (The Linux Foundation, USA-San Francisco CA)
Minimodul	© Lumberg Holding GmbH & Co. KG, DE-Schalksmühle
NI-XNET™	© National Instruments Corporation, USA-Austin TX
PCI Express®, PCIe®	© PCI-SIG, USA-Beaverton, OR
Visual Basic®, Visual C#®, Visual C++®, Windows®	© Microsoft Corporation, USA-Redmond WA